



ProBor 50.1 Wood Preservative Paste

Product Description

ProBor 50.1 Wood Preservative Paste is a dual action wood preservative and surface biocide. It is used to preserve wood from wood-rotting fungi and wood-destroying insects. It can be used for the treatment of large sectional timber and roof spaces. It is also effective against wood-boring insects. It can also be used as a surface biocide for the treatment of moulds, algae and fungi on internal surfaces such as masonry.

Benefits

Dual purpose

Excellent penetration

Solvent-free

Low odour

· Ready for use

Properties

Appearance	Clear liquid	
Size(s) & Packaging	400ml cartridges	
Coverage	Brush or Roller	Apply 1 litre per 2 - 2.5 m2 of surface
	Injection	Until refusal
Storage	Store above 10°C in dry conditions in original container. If the temperature falls below 10°C there is a risk that crystals may form in the product. If this occurs, the product should not be used. Store in a safe place, keep out of the reach of children. Keep away from food, drink and animal feedstuffs.	
Shelf Life	12 months	
Active Ingredient(s)	Disodium Octaborate (39.2 %w/w) Alkyl (C12-16) Dimethyl Ammonium Chloride (BACS) (1.25 %w/w)	
HSE Number	10632	
Re-entry Time	48 hours or until surfaces are dry	

Application Information

Preparation

The Control of Substances Hazardous to Health (COSHH) regulations apply to the use of this product at work. Ensure that the operator has read the relevant safety data sheet and



is wearing the appropriate safety equipment. Always read the label.

Application

ProBor 50.1 Wood Preservative Paste is injected into timber via pre-drilled holes, thus ensuring complete distribution of the active ingredient deep within the wood. The number of drill holes should be adjusted to give a product loading of 5.9 litres per cubic metre.

Drill 10 mm diameter holes at approximately 150 mm intervals into the timber being treated. Inject **ProBor 50.1 Wood Preservative Paste** into the drill holes using a standard mastic gun.

ProBor 50.1 Wood Preservative Paste can also be applied to the surface of timber by brush, although it should be noted that a white deposit will be left. Apply a generous brushed coat, taking special care to ensure that end grain, corners, joints and crevices are treated. Brush apply to surfaces exposed by cutting after treatment.

Other Information

For professional use only. For use only as a wood preservative. For full health and safety information consult safety data sheet. This product is approved for use under the Control of Pesticides Regulations (1986) for use as directed. HSE No.10632. Use pesticides safely. Always read the label.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.

Technical Datasheet Last modified 07/19 1 / 1