

Stormdry EP-Board Primer

Product Description

Stormdry EP-Board Primer is a liquid applied primer to aid adhesion of surface finishes such as paint and plaster to the MgO board.

Benefits

- Ready to use
- Can be painted or plastered over after 30 minutes

Properties

Appearance	clear to opaque (milky)
Density	1.0 g/cm ³ (approx.)
Sizes(s) & Packaging	1 litre jerry can
Coverage	10 m ² per litre
Storage	Protect from frost. Store above 5 °C



Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice; please ensure you have the latest updated information.

Application Instructions

All surfaces should be clean and free from dirt, grease, dust or other contaminants.

Apply one or two coats using brush or roller to the MgO board, ensure entire board surface is covered. Wait at least 30 minutes or until touch dry before applying any surface finish.

All equipment should be cleaned immediately after use with water. It is advisable that equipment should be cleaned/flushed during the course of application if breaks are expected during application.

Please refer to Stormdry EP-Board Application Guidelines for full details of how to apply.